



Outstanding Value. Exceptional Durability.

The new Go-Go® ES Scooter from Pride® delivers high-performance at an affordable price. The lightweight Go-Go ES features easy disassembly and Pride's exclusive black, non-scuffing tires. Designed for exceptional durability, the Go-Go ES provides reliability and outstanding value.



Easy disassembly.



Pride®
Mobility Products Corp.
— LIVE YOUR BEST —



Specifications

Model numbers	S83 (3-Wheel)
Max. weight capacity	275 lbs.
Maximum speed ¹	Up to 4 mph
Ground clearance ²	2.5" at mid-frame
Turning radius ²	32.75"
Overall length ²	38"
Overall width ²	19.5"
Tires	
Front	8" solid
Rear	8" solid
Anti-tips	Rear
Standard seating	Foldable, compact, vinyl-covered molded plastic
Drivetrain	24-volt DC motor, sealed mini-transaxle
Dual braking system	Electronic, regenerative and electromechanical
Battery charger	Off-board, 1.5 amp
Per-charge range ^{1,5}	Up to 6 miles
Battery requirements ³	(2) 12AH, 12V deep-cycle
Battery pack weight ⁴	16 lbs.
Weight w/o battery pack ²	72.5 lbs.
Heaviest piece ²	27.5 lbs. (front section)
Warranty	5-year limited on frame; 2-year limited on electronics; 1-year limited on motors

Standard colors



Red

Features

- Pride's exclusive black, non-scuffing tires
- Front frame-mounted seat post offers maximum stability
- Easily disassembles into 6 super lightweight pieces for convenient transport and storage
- Modular design for easy serviceability
- Convenient off-board dual voltage charger can charge battery pack on-board or off-board


Pride Lifts & Ramps

These Pride™ Lifts are compatible with the Go-Go® ES.

- Backpacker® Plus
- Backpacker® MV
- Power Tote Mini
- Outlander
- SilverBoom 250



Backpacker AVP



SilverBoom 250

Preliminary specifications; subject to change

¹Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. This specification can be subject to a variance of + or - 10%.

²Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³AGM or gel cell type required.

⁴Battery weight may vary based on manufacturer.

⁵This range was obtained with the 4-wheel model.

The information contained herein is correct at the time of publication. We reserve the right to alter specifications without prior notice.